## Relief Valves

## Features

- All wetted parts are 316SS or Carpenter 20
- Pressures from 30 to 2000 psi
- Spring guide for consistent relief capacity
- Easily adjustable relief setting
- Liquid service only


Neptune Relief Valves have two outstanding characteristics:

economy simplicity

Economy. Models RV-316-1, -2, -3 and -4 with all 316SS wetted parts cost no more than other 304SS designs. Carpenter 20 valves are also available as standard.

**Simplicity.** Neptune's exclusive design uses a self-cleaning ball check and seat. It has a unique spring guide which assures proper spring loading and consistent relief capacity. The relief pressure setting can be easily changed by removing the top cap screw and locking set screw, inserting a proper Allen wrench into the opening, and adjusting the spring to the desired pressure.

Recommended setting: Operating pressure plus 10% or 50 psi whichever is greater.



## **SPECIFICATIONS** Inlet/Outlet pipe size: ½" NPT

MODEL NUMBER	PRESSURE (PSI)	CAPACITY (GPM)
RV-316-1 RV-C20-1	100	3.0
RV-316-2 RV-C20-2	400	4.0
RV-316-3	1000	4.0
RV-316-4	2000	6.0

## **Quotation and Ordering Information**

Please supply the following information:

- 1. Type of liquid to be handled.
- 2. Relief pressure range or set point required.





MATERIAL OF CONSTRUCTION	MODEL NUMBER	PRESSURE RANGE (PSI)
Type 316 Stainless Steel	RV-316-1 RV-316-2 RV-316-3 RV-316-4	30 to 100 101 to 400 401 to 1000 1001 to 2000
Carpenter 20	RV-C20-1 RV-C20-2	30 to 100 101 to 400



SOLD BY: